

tutorial

L^AT_EX in proper ConT_EXt

Berend de Boer
berend@pobox.com

1	ConT _E Xt for L ^A T _E X users	65
2	ConT _E Xt basics	66
3	Common L ^A T _E X Environments	68
4	Floats	74
5	Tables	76
6	Math	78
7	Changing the layout	79
8	References	85
9	Interactive documents	86
10	Other	87
11	Understanding ConT _E Xt	88
12	L ^A T _E X commands	89
13	ConT _E Xt commands	90
14	L ^A T _E X to ConT _E Xt reference	91

1 ConT_EXt for L^AT_EX users

1.1 For who is this document

If you are a L^AT_EX user, switching to an entirely different macro–package is a very big step. Everything you put so much effort in to learn, doesn’t work anymore.

I can’t help but quote from that famous book “The psychology of computer programming” (chapter 11):

In making our adjustments to our particular programming language, we can easily become attached to it simply because we now have to much invested in it. We often listen to a man complaining about his nagging, slovenly, and prodigal wife, only to find that when asked why he doesn’t leave her, he replies that he cannot live without her. Most people would prefer almost any amount of pain to giving up the familiarity of some constant companion for an unknown quantity. We see this effect when we try to teach a programmer his *second* language. Teaching the first is no great problem, for he has no investment in any other. By the time he has learned two or more, he is aware that more things exist in this world than he has dreamed of. But letting go of the first is, to him, just a promise of pain with no promise of compensating pleasure.

To help lessen the pain for users make the switch, this document shows short L^AT_EX code snippets and how you do the same in ConT_EXt.

ConT_EXt is a macro package that’s far more advanced than L^AT_EX. You can enhance L^AT_EX with third party packages, but not all macro packages work together with each other. ConT_EXt is an integrated, powerful and flexible macro package for which you seldom need third party packages. ConT_EXt also has been used to create large and complex on–screen documents, including hyperlinks, on screen buttons, forms, cross–document links, and so on.

This document is not a reference to the ConT_EXt manual. It only shows you the ConT_EXt macros for the familiar L^AT_EX macros. It does not explain the ConT_EXt

macros in detail nor shows you the numerous options almost every command has. You are referred to the <http://www.pragma-ade.nl/general/manuals/beta/cont-nli.pdf> instead.

1.2 References

If you take up ConT_EXt, you probably need help. You can find it at the following locations:

- The ConT_EXt support site is <http://www.pragma-ade.nl>.
- There is a beginner's manual in english at <http://www.pragma-ade.nl/zipped/bman-en.zip>.
- ConT_EXt main reference however is still in dutch and can be found at <http://www.pragma-ade.nl/general/manuals/beta/cont-nli.pdf>.
- The 4T_EX manual also contains much material on ConT_EXt, see <http://4tex.ntg.nl/4tex5>.
- There is a ConT_EXt mailling list. Subscribe by sending a message to <mailto:ma-jordomo@ntg.nl>. In the body of the message type:

```
subscribe ntg-context yourname@yourserver.yourdomain
```

1.3 Acknowledgements

Thanks to David Arnold, Wybo Dekker and Hans Hagen for offering suggestions and sending corrections to this document.

2 ConT_EXt basics

This chapter tells you ConT_EXt's basics.

2.1 A basic document

A basic 'hello world' kind of document in L_AT_EX looks like:

```
\documentclass{article}
\begin{document}
Hello world.
\end{document}
```

In ConT_EXt it looks like:

```
\starttext
Hello world.
\stoptext
```

ConT_EXt does not have a special command to load the style for a certain document. If you have them, you can load style files and such with the T_EX macro `\input`.

2.2 Compiling your document

If your L_AT_EX 'Hello world' document is called `text.tex`, you probably compile your document with:

```
latex test.tex
```

In ConT_EXt you use a wrapper around the T_EX compiler to compile your document. Your ConT_EXt document is compiled with:

```
texexec test.tex
```

`texexec` also takes care of the table of contents, indexes, references and sorted lists (see also section 11.1). It recompiles your document as many times as necessary to make sure references in the document are ok.

While you could use something as:

```
context test.tex
```

to compile your document, this is not advised. Learn to use `texexec`:

```
texexec test.tex
```

The first output of `texexec` should look like:

```
TeXExec 1.9 - ConTeXt / PRAGMA ADE 1997-2000
      executable : pdfetex
      format     : cont-en
      inputfile  : test
      output     : dvips
      interface  : en
      current mode : all
      TeX run   : 1
```

and then it starts compiling your document.

ConT_EXt supports various language specific interfaces. This document presents the english language interface but ConT_EXt also has a dutch and german based interface. If the default interface on your system is not correct, you can either change the initialization file `texexec.ini` or give a parameter to `texexec`:

```
texexec -interface=en test.tex
```

ConT_EXt supports also various output formats like `.dvi` and `.pdf`. To generate a `.pdf` document instead of a `.dvi` document, change `texexec.ini` or call `texexec` with the following parameter:

```
texexec -output=pdfetex test.tex
```

Or even shorter with:

```
texexec --pdf test.tex
```

Probably the best option is to put the `texexec` parameters as the first line in your document like:

```
% interface=en output=pdfetex
\starttext
This example compiles with the english interface and
generates pdf output.
\stoptext
```

2.3 Chapters and sections

Chapters and sections in ConT_EXt are very much like L^AT_EX. In L^AT_EX you write:

```
\documentclass{report}
\begin{document}
\chapter{One}
My first chapter.
\chapter{Two}
My second chapter.
\end{document}
```

In ConT_EXt this looks like:

```
\starttext
\chapter{One}
My first chapter.

\chapter{Two}
My second chapter.

\stoptext
```

Not much difference here. However, referencing to chapters or sections is done differently in ConT_EXt, see section 8.1.

2.4 Table of contents

A table of contents in L_AT_EX is done with the `\tableofcontents` command:

```
\documentclass{report}
\begin{document}
\tableofcontents
\chapter{One}
My first chapter.
\chapter{TwoOne}
My second chapter.
\end{document}
```

In ConT_EXt you get a table of contents with the `\completecontent` command:

```
\starttext
\completecontent
\chapter{One}
My first chapter.
\chapter{Two}
My second chapter.
\stoptext
```

Remember to compile with `texexec`, or else you will not get the table of contents (see section 11.1). Besides `\completecontent`, ConT_EXt also has `\placecontent`. `\completecontent` starts a new page, while `\placecontent` doesn't.

3 Common L_AT_EX Environments

In the following sections the most common L_AT_EX environments are discussed and ConT_EXt alternatives are given. Environments are discussed in alphabetic order.

3.1 The abstract environment

With L_AT_EX's abstract environment you can mark one or more paragraphs in some special way. It also depends on the documentclass you have loaded, either article or report. Its layout is equal to the quotation environment.

You use `abstract` as follows:

```
\documentclass{article}
\begin{document}

\begin{abstract}
This is an abstract of this article.
\end{abstract}

\end{document}
```

There is no `abstract` environment in ConT_EXt, because it really is a style option. However, you can get the same effect as L^AT_EX's `article` `abstract` environment with:

```
\starttext

\startnarrower\switchtobodyfont[small]
\midaligned{\bf Abstract}\par
This is an abstract of this article.
\stopnarrower

\stoptext
```

With `\startnarrower` you get a paragraph, left and right indented by some white space. With `\switchtobodyfont` you get a font somewhat smaller than the current body font. With `\midaligned` you get a centered line.

3.2 The bibliography environment

In L^AT_EX you can create a bibliography within the `thebibliography` environment:

```
\documentclass{article}
\begin{document}

\section{My life}

I've read only two books in my life \cite{Bekke92}, \cite{Brodie84}.

\begin{thebibliography}{Brodie84}

\bibitem[Bekke92]{Bekke92}
  J.H.~ter~Bekke, \emph{Semantic datamodeling}, Prentice Hall, Hemel
  Hempstead, ISBN~0-13-806050-9, 1992.

\bibitem[Brodie84]{Brodie84}
  L.~Brodie, \emph{Thinking Forth, a language and philosophy for
  solving problems}, Prentice Hall, ISBN 0-13-917568-7, 1984.

\end{thebibliography}

\end{document}
```

Entries are started with `\bibitem` and appear in the `thebibliography` environment. Entries are referred to with the `\cite` command.

In ConT_EXt, bibliographies are supported by the `bib` module. This module is not yet in the standard release, you have to download it separately at <http://www.cybercomm.nl/~bitttext/temp/m-bib.zip>. See section 11.2 on how to generate the documentation for this module. It seems the documentation is a bit ahead of the implementation, but expect the module to improve over the course of the next few months.

In ConT_EXt, references have to be in a separate file. For this example it is easiest to have them in a file with the same name, but with the .bb1 extension.

An example of such a file is:

```
\startpublication[k=Brodie84,
                 t=article,
                 a=L.~Brodie,
                 y=1984,
                 s=LB84]
\artauthor[] {Leo} [L.] {} {Brodie}
\arttitle{Thinking Forth, a language and philosophy for solving
          problems}
\journal{Prentice Hall}
\pubyear{1984}
\stoppublication

\startpublication[k=Bekke92,
                 t=article,
                 a=J.H.~ter~Bekke,
                 y=1992,
                 s=JB92]
\artauthor[] {Johan} [J.H.] {ter} {Bekke}
\arttitle{Semantic datamodeling}
\journal{Prentice Hall}
\pubyear{1992}
\stoppublication
```

Entries are started with the `\startpublication` command.

Having this file, it is now possible to use them as follows:

```
\usemodule[bib]

\setuppublications
 [numbering=yes,
 sort=author]

\starttext

\section{My life}

I've read only two books in my life \cite[Bekke92,Brodie84]. But I've
admit that I no longer think Forth \cite[Brodie84].

\completepublications

\stoptext
```

The command `\setuppublications` is optional. It defines such things as which entries to include, how to sort them or to include every entry or only the referenced ones. It currently does not seem possible to mimick the way L^AT_EX references things.

With `\completepublications` the list of publications is given. And of course there is also a `\placepublications` command which does not add something to the table of contents.

For bibT_EX information, see section 8.4.

3.3 The description environment

L^AT_EX's description environment produces a list where each label is a keyword instead of a bullet or a number.

```
\documentclass{article}
\begin{document}

\begin{description}
\item[gnat] A small animal, found in the North Woods, that causes no
end of trouble.
\item[gnu] A large animal, found in crossword puzzles, that causes no
end of trouble.
\item[armadillo] A medium-sized animal.
\end{description}

\end{document}
```

In ConT_EXt you use the `\definedescription` command to setup an environment. A description is not an enumeration like it is in L^AT_EX. In the following code we first define the environment, called `animal`. It's also possible to define the environment `description`, but that's quite confusing. In the main text we show how this new environment is used:

```
\definedescription
[animal]
[location=hanging,
margin=standard,
headstyle=bold]

\definestartstop
[animals]
[before=\blank\startpacked,
after=\stoppacked\blank]

\starttext

\startanimals
\animal{gnat} A small animal, found in the North Woods, that
causes no end of trouble.

\animal{gnu} A large animal, found in crossword puzzles, that
causes no end of trouble.

\startanimal{armadillo}
A medium-sized animal.
\stopanimal

\stopanimals

\stoptext
```

Within `\startanimals`, descriptions (`animals`) can be given. You can use both `\animal` or `\startanimal` to define a description. The start/stop pair is of course more robust. The type `\animal` expects a `\par` (or empty line) to work.

The use of `\definestartstop` is optional, but this helps to clearly mark the definition of animals and to have a common point of settings like white space before and after. With `\blank` we get the default blank space before (the space between paragraphs). With `\startpacked` we get paragraphs that do not have white space between them.

A different solution, however without the hanging indent feature, is:

```

\starttext
\startitemize[4*broad,packed]
\sym{gnat} A small animal, found in the North Woods, that causes no
end of trouble.
\sym{gnu} A large animal, found in crossword puzzles, that causes no
end of trouble.
\sym{armadillo} A medium-sized animal.
\stopitemize
\stoptext

```

In this example, the text `armadillo` overlaps with its definition if the margin is not defined sufficiently large. So the first solution is better.

This example also shows ConT_EXt's way of setting options. With `4*broad` we set the width of the symbol to four times the `broad` setting. With `packed` we specify that we don't want white space between paragraphs.

3.4 The enumerate environment

L^AT_EX's `enumerate` environment is used to produce a numbered list:

```

\documentclass{article}
\begin{document}
\begin{enumerate}
\item First item.
\item Second item.
\end{enumerate}
\end{document}

```

In ConT_EXt lists, both numbered and unnumbered, are started with `\startitemize`. You use the `n` option to produce a numbered list:

```

\starttext
\startitemize[n]
\item First item.
\item Second item.
\stopitemize
\stoptext

```

See also the example in section 3.5. See section 7.9 for how to influence the layout of lists.

3.5 The itemize environment

L^AT_EX's `itemize` environment is used to produce an unnumbered list:

```

\documentclass{article}
\begin{document}
\begin{itemize}
\item First item.
\item Second item.
\end{itemize}
\end{document}

```

Every line starts with a bullet.

In ConT_EXt lists, both numbered and unnumbered, are started with `\startitemize`. If you don't use an option, you get an unnumbered list:

```
\starttext
\startitemize
\item First item.
\item Second item.
\stopitemize
\stoptext
```

See also the example in section 3.4. See section 7.9 for how to influence the layout of lists.

3.6 The quotation environment

You can quote someone in L^AT_EX with the `quote` environment:

```
\documentclass{article}
\begin{document}
\begin{quote}
  But letting go of the first is, to him, just a promise
  of pain with no promise of compensating pleasure.
\end{quote}
\end{document}
```

In ConT_EXt you achieve the same effect with the `\startquotation` command:

```
\starttext
\startquotation
  But letting go of the first is, to him, just a promise
  of pain with no promise of compensating pleasure.
\stopquotation
\stoptext
```

L^AT_EX also has a quotation environment used for quotations of more than one paragraph.

In ConT_EXt you can always use `\startquotation`.

ConT_EXt also has 'inline' quotes. Use either its `\quote` or `\quotation` command:

```
\starttext
This is a \quote{quote} and this is a \quotation{quotation}.
\stoptext
```

`\quote` surrounds your quote with single quote characters, `\quotation` surrounds your quote with double quote characters.

3.7 The verbatim environment

Verbatim text (text not subject to macro expansion) in L^AT_EX is done with the `verbatim` environment:

```
\documentclass{article}
\begin{document}
\begin{verbatim}
This is
```

```
verbatim \LaTeX.
\end{verbatim}

\end{document}
```

In ConT_EXt you write this as:

```
\starttext

\starttyping
This is
verbatim \ConTeXt.
\stoptyping

\stoptext
```

4 Floats

Floats are pieces of text that do not follow the main flow, but can go on the same page or elsewhere. ConT_EXt has very extensive support for them.

4.1 Figures

In L_AT_EX you can include a bitmap if you use the `graphics` or `graphicx` package. With the `\includegraphics` command you can include a bitmap.

If you use `pdftex`, you can now define a figure as simply as:

```
\documentclass{article}

\usepackage[pdftex]{graphicx}

\begin{document}

\begin{figure}
\includegraphics{test.png}
\caption{Test picture}
\label{fig:test}
\end{figure}

\end{document}
```

This figure also has a caption and it has a label so you can refer to it. In ConT_EXt you do this with:

```
\starttext

\placefigure
[]
[fig:test]
{Test picture}
{\externalfigure[test.png]}

\stoptext
```

Probably the size of the figure differs between L_AT_EX and ConT_EXt. In ConT_EXt figures have their natural size by default. You can influence the scaling of a figure with the `scale` option:

```
\starttext
```

```

\placefigure
[]
[fig:test]
{Test picture}
{\externalfigure[test.png][scale=2000]}

\stoptext

```

The default scale is **1000 (100%)**. Scale **2000** gives you a figure twice as large. You can also specify the width of the figure in dimensions, for example half the text width (see example below).

In ConT_EXt you usually define your figures at the top of your file, above the `\starttext` command. You can recall them when needed:

```

\useexternalfigure
[testone]
[test.png]
[scale=2000]

\useexternalfigure
[testtwo]
[test.png]
[width=.5\textwidth]

\starttext

\placefigure
[]
[fig:testone]
{Test picture: twice as large as it natural size}
{\externalfigure[testone]}

\placefigure
[]
[fig:testtwo]
{Test picture: half as large as the text}
{\externalfigure[testtwo]}

\stoptext

```

With `\useexternalfigure` the first command is the name of the macro you want to define, the next is the name of the file. The third parameter are scaling and sizing options.

In <http://www.pragma-ade.nl/zipped/bman-en.zip> you can find more things you can do with figures like placing two figures together or placing text left or right of a figure.

4.2 List of figures

A list of figures in L^AT_EX can be given with its `\listoffigures` command:

```

\documentclass{article}
\usepackage[pdftex]{graphicx}

\begin{document}

\listoffigures

\begin{figure}
\includegraphics{test.png}

```

```

\caption{Test picture}
\label{figure:test}
\end{figure}

\end{document}

```

In ConT_EXt you use the `\completelistoffigures` command:

```

\starttext

\completelistoffigures

\placefigure
  [fig:test]
  {Test picture}
  {\externalfigure[test.png]}

\stoptext

```

Just like `\completecontent`, besides `\completelistoffigures` there also is a `\placelistoffigures` command which doesn't start a new page.

Be aware that `\completelistoffigures` only works at the beginning of a document, not at the end. There probably is a workaround, and as soon as I know it, I'll say so here.

5 Tables

5.1 The tabular environment

In L^AT_EX tables are defined with the `tabular` environment environment. A famous L^AT_EX example demonstrating many of its features is:

```

\documentclass{article}

\begin{document}

\begin{tabular}{|r|r@{--}l|p{1.25in}|}
\hline
\multicolumn{4}{|c|}{GG&A Hoofed Stock}
  \ \ \hline\hline
&\multicolumn{2}{c|}{Price}& \ \ \cline{2-3}
\multicolumn{1}{|c|}{Year}
& \multicolumn{1}{r@{\, \vline\,}}{low}
& high & \multicolumn{1}{c|}{Comments}
  \ \ \hline
1971 & 97 & 245 & Bad year for
      farmers in the west. \ \ \hline
72 & 245 & 245 & Light trading due to a
      heavy winter. \ \ \hline
73 & 245 & 2001 & No gnus was very
      good gnus this year. \ \ \hline
\end{tabular}

\end{document}

```

In ConT_EXt tables are created within the `\starttable` environment:

```

\starttext

\starttable[|r|r|1|p{1.25in}|]
\HL

```

```

\VL \FOUR{GG\&A Hoofed Stock} \VL\SR
\HL
\VL \LOW{Year} \VL \TWO{Price} \VL \LOW{Comments} \VL\SR
\DC          \DL[2]          \DC          \DR
\VL          \VL low \VL high \VL          \VL\SR
\HL
\VL 1971 \VL \TWO{97--245} \VL
    Bad year for farmers in the west. \VL\SR
\HL
\VL 72 \VL \TWO{245--245} \VL
    Light trading due to a heavy winter. \VL\SR
\HL
\VL 73 \VL \TWO{245--2001} \VL
    No gnus was very good gnus this year. \VL\SR
\HL
\stoptable
\stoptext

```

In ConT_EXt you can use `\starttables` to create a table that can be split across pages.. In L^AT_EX this is provided by the `longtable` environment, provided by an external package.

5.2 The tabbing environment

To align data vertically, one can use the `tabbing` environment in L^AT_EX. It's usage is quite complex, only a simple example is given:

```

\documentclass{article}
\begin{document}
\begin{tabbing}
    Armadillo: \= \kill
    Gnat: \> not edible \\
    Armadillo: \> not edible\\
\end{tabbing}
\end{document}

```

The same example in ConT_EXt using its `\starttabulate` environment:

```

\starttext
\starttabulate[|l|p|]
\NC Gnat: \NC not edible \NC\NR
\NC Armadillo: \NC not edible \NC\NR
\stoptabulate
\stoptext

```

In L^AT_EX the first line more or less determines the format (but can be changed in later lines). In ConT_EXt the `\starttabulate` environment works more or less like its `\starttable` environment. The header specifies the format of the columns. The width of the columns will be equal to the header with the largest contents. You can also explicitly specify the width.

Every row starts with `\NC` (next column). Every row ends with a `\NC` and `\NR` (next row).

The difference between ConT_EXt's `\starttabulate` and `\starttable` environments are that the former splits across pages. And the `p` column type is a bit smarter in the `\starttabulate` environment. The drawback of `\starttabulate` is, that it does not support vertical lines.

5.3 List of tables

In \LaTeX one gets the list of tables with the `\listoftables` command. Only tables placed within the `table` environment are put in the table of contents.

In \ConTeXt one uses the `\placelistoftables` command. And as in \LaTeX , only tables given as argument to `\placetable` are put in the table of contents.

6 Math

6.1 General

Math in \ConTeXt and \LaTeX is not that different. Both depend mostly on \TeX . \LaTeX adds some environments for doing math. \ConTeXt is mostly very close to \TeX . In \ConTeXt probably every \TeX math command just works.

6.2 In-text formulas

In \ConTeXt in-text formula's are produced by surrounding the formula by the `$` character.

6.3 Display style formulas

In \ConTeXt display style formula's are produced by surrounding the formula by two `$` characters. You can also use the `\startformula` environment for exactly the same effect.

6.4 Numbered formulas

With \LaTeX numbered formula's are made within the `equation` environment:

```
\documentclass{article}
\begin{document}
\begin{equation}
E = mc^2
\end{equation}
\end{document}
```

In \ConTeXt numbered formulas are produced to prefix the display formula command with `\placeformula`.

```
\starttext
\placeformula $$ E = mc^2 $$
\stoptext
```

6.5 Multiline formulas

In \LaTeX multiline formula's are produced with the `eqnarray` environment. A new line is started after the `\\` command.

In \ConTeXt you use \TeX 's `displaylines` command. A new line is started after the `\cr` command.

```
\starttext
$$\displaylines{%
  ZeroOrOne = ( ( Amount\ mod\ Currency_RoundingFactor )\cr
  +\ Currency_Boundary )\cr
  div\ Currency_RoundingFactor}$$
\stoptext
```

6.6 Theorems and such

\LaTeX has the `\newtheorem` command to define environments for theorems-like structures. You would use it as follows:

```

\documentclass{article}
\newtheorem{guess}{Conjecture}
\begin{document}
This is the first one:
\begin{guess}
  All conjectures are interesting.
\end{guess}
\end{document}

```

With ConT_EXt you would use the `\defineenumeration` command. This command has many options, the following settings make it more or less equal to L^AT_EX's `\newtheorem`:

```

\defineenumeration
[guess]
[text=Conjecture,
location=left,
letter=it]
\starttext
This is the first one:
\guess All conjectures are interesting.

This is the second one:
\startguess Except this one. \stopguess
\stoptext

```

As can be seen both `\guess` and `\startguess` can be used. Also `\subguess`, `\subsubguess` and so on are now available.

ConT_EXt's `\defineenumeration` can be used for any kind of thing you want to enumerate.

7 Changing the layout

As soon as you are able to write basic documents, you probably want to change their appearance. This chapter documents the differences between L^AT_EX and ConT_EXt. As ConT_EXt is a very, very flexible macro package, this is one of the largest chapters. Almost everything can be customized, you just call `\setupsomething`.

7.1 Page size

In L^AT_EX you give the page size as an option to the `\documentclass` command:

```

\documentclass[a4paper]{article}
\begin{document}
\end{document}

```

In ConT_EXt you use the `\setuppapersize` command.

```

\setuppapersize[A4]
\starttext
\stoptext

```

With ConT_EXt it is possible to do far more advanced things. You can typeset in A5 and print on A4 for example.

7.2 Fonts

Changing the font size in \LaTeX is usually done with a document class option:

```
\documentclass[12pt]{report}
\begin{document}
\end{document}
```

In \ConTeXt you use the `\setupbodyfont` command:

```
\setupbodyfont[12pt]
\starttext
\stoptext
```

Use `\setupbodyfont` only to set the document font. To switch to another font during typesetting, you should use `\switchtobodyfont`.

To switch to a postscript font in \LaTeX , you can use certain packages. To switch to a Helvetica body font you would type:

```
\documentclass{article}
\usepackage{helvet}
\begin{document}
\end{document}
```

In \ConTeXt you accomplish the same with the `\setupbodyfont` command:

```
\setupbodyfont[ber,phv,ss]
\starttext
\stoptext
```

With the option `ber` you specify that you want to use Karl Berry fontnames. With `phv` you specify that you want to load the Helvetica font definitions, and with `ss` you specify that you want to use a sans-serif font as the body font.

To switch to the default postscript fonts `times`, `helvetica` and `courier`, you would say:

```
\setupbodyfont[ber,pos]
\starttext
\stoptext
```

7.3 Interline spacing

To change the interline spacing in \LaTeX you change the `baselineskip` variable:

```
\documentclass{article}
\setlength\baselineskip{12pt}
\begin{document}
\end{document}
```

This changes the distance between lines to 12pt, a good value for a 10pt font. As in \LaTeX , if you change the size of the body font in \ConTeXt , the line skip is automatically recalculated. You can set it yourself with `\setupinterlinespace`:

```
\setupinterlinespace[line=1.2\bodyfontsize]
```

```
\starttext
\stoptext
```

Be careful to always define the `interlineskip` in terms of the current `\bodyfontsize`, else you get unexpected results when the `\bodyfontsize` changes, for example in chapter headings.

7.4 Spacing between paragraphs

To change the interparagraph spacing in L^AT_EX, you change the `\parskip` variable:

```
\documentclass{article}
\setlength{\parskip}{3pt}

\begin{document}
This is my first paragraph.

This is my second paragraph.
\end{document}
```

This gives you 3 extra points of white space between paragraphs. In ConT_EXt you use the `\setupwhitespace` command.

```
\setupwhitespace[3pt]

\starttext
This is my first paragraph.

This is my second paragraph.
\stoptext
```

However, instead of a fixed size specification, it is much better to use current font size related specifications like `medium` or `big`:

```
\setupwhitespace[medium]

\starttext
This is my first paragraph.

This is my second paragraph.
\stoptext
```

7.5 Paragraph indentation

In L^AT_EX every paragraph has some white space at the beginning of its first line. You can disable this by setting the amount of white space to 0:

```
\documentclass{article}
\setlength{\parindent}{0pt}

\begin{document}
This is my first paragraph. This is my first paragraph. This is my
first paragraph. This is my first paragraph. This is my first
paragraph. This is my first paragraph.

This is my second paragraph.
\end{document}
```

ConT_EXt doesn't start with white space. To start a paragraph with some white space say:

```
\setupindenting[medium]

\starttext
This is my first paragraph. This is my first paragraph. This is my
first paragraph. This is my first paragraph. This is my first
paragraph. This is my first paragraph.

This is my second paragraph.

\stoptext
```

7.6 Position of the page number

In L_AT_EX the position of the page number can be set with the `\pagestyle` command. In ConT_EXt you use the `\setuppagenumbering` command.

There are four L_AT_EX page styles. The corresponding ConT_EXt settings are given below:

1. `\pagestyle{plain}`:

```
\setuppagenumbering[location={footer,middle}]
```

2. `\pagestyle{empty}`:

```
\setuppagenumbering[location=]
```

3. `\pagestyle{headings}`:

```
\setuppagenumbering[location={header,middle}]
```

4. `\pagestyle{myheadings}`:

```
\setuppagenumbering[location=header]
```

(see ...)

Note that in ConT_EXt a page consists of much more than L_AT_EX's three default units *head*, *body* and *foot*, so you have much more options.

7.7 Roman and arabic pagenumbers

In L_AT_EX Roman and Arabic page numbers are specified with the `\pagenumbering` command.

```
\documentclass{article}

\begin{document}

\pagenumbering{roman}
\tableofcontents

\chapter{Introduction}
\pagenumbering{arabic}
This is a test.

\end{document}
```

In ConT_EXt you use the `\setupnumbering` command.

```
\startfrontmatter
```

```

\setuppagenumbering[conversion=romannumerals]
\setuppagenumber[number=1]
\completecontent

\stopfrontmatter

\startbodymatter

\setuppagenumbering[conversion=numbers]
\setuppagenumber[number=1]
\chapter{Introduction}
This is a test.

\stopbodymatter

```

This example also shows a typical document structure by its use of `\startfontmatter` and `\startbodymatter`. The front matter has roman page numbers, the body matter arabic ones. We also use `\setuppagenumber` to start counting from 1 for each of the sections. The first `\setuppagenumber` could be omitted, but typically you have a front page and such, so page numbering starts a bit later than the first physical pages.

7.8 Setting up chapter and sections

In L^AT_EX changing the format of chapters and sections is not possible unless you change L^AT_EX internal commands. Therefore, no examples of doing this in L^AT_EX are given, but only the ConT_EXt options are demonstrated.

Every section heading can be setup with ConT_EXt's `\setuphead` command. Probably one of the first things you want to change is the font used for the chapters and sections.

```

\setuphead[chapter][letter={\switchtobodyfont[20pt,ss]\bf}]
\setuphead[section][letter={\switchtobodyfont[16pt,ss]\bf}]

\starttext

\chapter{This is a chapter}

First sentence.

\section{This is a section}

First sentence.

\stoptext

```

This gives you a **20** points, bold, sans serif font for chapter headings.

It is possible to define that you want to start a chapter on a right page:

```

\setuppagenumbering[alternative=doublesided]
\setuphead[chapter]
  [page=right]

\starttext

\chapter{First thought}

First sentence.

\chapter{Second thought}

Second sentence.

\stoptext

```

You also need to turn doublesided pagenumbering on with `\setuppagenumbering`. Now every chapter starts on an uneven numbered page.

The following example changes even more. The number is set in a different font, and before and after the chapter is set, we execute our own commands.

```
\setuphead
  [chapter]
  [numberstyle=bold,
  textstyle=cap,
  before=\hairline\blank,
  after={\nowhitespace\hairline\blank[line]}]

\starttext

\chapter{This is a chapter}

A sentence.

\stoptext
```

Note that almost any(!) setup command has before and after options, so really everything in ConT_EXt can be changed easily.

It is also possible to format the entire section heading yourself. The following example formats the subsection heading. You need to write a macro which expects two parameters: the number of that section and the title of that section. And then you're on your own.

```
\setuphead
  [subsection]
  [command=\myhead]
  \def\myhead#1#2{#2}

\starttext

\chapter{This is a chapter}

\section{Section}

\subsection{Yes}

A sentence.

\stoptext
```

Note that turning off the number is a standard option, so this setup can also be accomplished with:

```
\setuphead
  [subsection]
  [number=no]

\starttext

\chapter{This is a chapter}

\section{Section}

\subsection{Yes}

A sentence.

\stoptext
```

7.9 Setting up lists

Enumerations in ConT_EXt have white space between each items. You can disable this by using the packed option.

```
\setupitemize[packed]
\starttext
\startitemize[n]
\item First line.
\item Second line, no white space above it.
\stopitemize
\stoptext
```

8 References

8.1 In document references

8.2 Cross document references

8.3 Index

In L^AT_EX producing indexes is a two step process. In the preamble you put the `\makeindex` command so an index file (`.idx`) is created. The contents of every `\index` command is put into that file. Next the `makeindex` command is used to produce the actual index which can be included in your document with the `\input` command.

```
\documentclass{article}
\makeindex
\begin{document}
Put \index{this} and \index{that} in the index.
\input{testlatex.ind}
\end{document}
```

In ConT_EXt creating indexes is also a two step process, but this is transparent if you use `texexec` to compile your documents. With the `\index` command you put entries in the index, with `\completeindex` you get the entire index at that point.

```
\starttext
Put \index{this} and \index{that} in the index.
\completeindex
\stoptext
```

8.4 bibtex

You can use `bibtex` to produce `.bbl` files as usual. The new `bib` module (see section 3.2) can read `.bbl` files fine. You can specify on or more databases in `\setuppublications` after the database keyword.

```
\usemodule[bib]
\setuppublications
[database={mybibs},
numbering=yes,
sort=author]
```

```

\starttext
\section{My life}
I've read only two books in my life \cite[laan95:_types_pascal].
But I've admit that I no longer think Forth \cite[wogan:73a].
\completepublications
\stoptext

```

However, bib support is not yet foolproof.

9 Interactive documents

9.1 Defining an interactive document

```

\usepackage{article}
\usepackage
  [pdftitle={Test document},
  pdfauthor={Berend de Boer},
  pdfsubject={There is more than LaTeX},
  pdfkeywords={LaTeX ConTeXt TeX},
  colorlinks,
  linkcolor=blue]
{hyperref}
\begin{document}
\end{document}

```

```

\setupinteraction
  [status=start,
  title={Test document},
  author={Berend de Boer},
  subtitle={There is more than LaTeX},
  keywords={LaTeX ConTeXt TeX},
  color=blue]
\starttext
\stoptext

```

9.2 References which are URLs

In L^AT_EX the hyperref package provides hyperlinking support. To generate a URL reference, you use the \href command:

```

\documentclass{article}
\usepackage{hyperref}
\begin{document}
The \href{http://www.freebsd.org}{greatest server OS} on this world.
\end{document}

```

```

\setupinteraction[state=start]

```

```

\useURL
[contextsupport]
[http://www.pragma-ade.nl]

\starttext

The \ConTeXt\ support site is \from[contextsupport].

\stoptext

```

10 Other

10.1 Title page

10.2 Text in margin

10.3 Color

You can enable color with the `\setupcolors` command.

```

\setupcolors[state=start]

\starttext

\stoptext

```

10.4 Babel

10.5 Interfaces

10.6 Breaking lines

10.7 Vertical white space

If you need vertical white space, L^AT_EX has the `\vspace` command. This command only works between paragraphs. At the beginning and end of a page white space ‘disappears’, use `\vspace*` for white space that does not disappear.

```

\documentclass{article}

\begin{document}
\vspace*{5cm}
This line comes first.

\vspace{2\baselineskip}

This line comes second.

\vspace{.5\baselineskip}

And this is the third line.

\end{document}

```

In ConT_EXt the `\blank` command gives blank space. It also ends the preceding paragraph. Use the `force` option to force white space at the beginning and end of a page.

```

\starttext
\blank[5cm,force]
This line comes first.
\blank[2*line]
This line comes second.
\blank[medium]

```

```
And this is the third line.  
\stoptext
```

11 Understanding ConT_EXt

11.1 texexec

ConT_EXt uses the external program `texexec` to do lots of things which are more difficult to do directly in T_EX:

1. ConT_EXt writes its table of contents entries to a `.tui` file. If the compilation went fine, `texexec` copies this to the corresponding `.tuo` file.
This means that when a compilation does not run to completion (you cancel it for example), the table of contents entries and references have not disappeared.
2. `texexec` sorts indexes and sorted lists.

11.2 Module documentation

Generate ConT_EXt module documentation with:

```
texexec --module m-bib
```

You need to have the documentation styles which can be downloaded from <http://www.pragma-ade.nl>, filename `cont-doc.zip`.

12 L^AT_EX commands

List of L^AT_EX commands used in this document.

b	<code>\listoftables</code> 78
<code>\bibitem</code> 69	<code>longtable</code> environment 77
<code>bibliography</code> environment 69	
c	m
<code>\cite</code> 69	<code>\makeindex</code> 85
<code>comment</code> environment 92	n
	<code>\newtheorem</code> 78, 79
d	p
<code>description</code> environment 71	<code>\pagenumbering</code> 82
<code>\documentclass</code> 79	<code>\pagestyle</code> 82
e	<code>\parskip</code> 81
<code>enumerate</code> environment 72	q
<code>eqnarray</code> environment 78	<code>quotation</code> environment 73
<code>equation</code> environment 78	<code>quote</code> environment 73
h	t
<code>\href</code> 86	<code>tabbing</code> environment 77
i	<code>table</code> environment 78
<code>\includegraphics</code> 74	<code>\tableofcontents</code> 68
<code>\index</code> 85	<code>tabular</code> environment 76
<code>\input</code> 85	
<code>itemize</code> environment 72	v
l	<code>\vspace</code> 87
<code>\listoffigures</code> 75	<code>\vspace*</code> 87

13 ConT_EXt commands

List of ConT_EXt commands used in this document.

b	<code>\placepublications</code> 70
<code>bib module</code> 85, 91	<code>\placetable</code> 78
<code>\blank</code> 71, 87	
<code>\bodyfontsize</code> 81	
c	q
<code>\completecontent</code> 68, 76	<code>\quotation</code> 73
<code>\completeindex</code> 85	<code>\quote</code> 73
<code>\completelistoffigures</code> 76	
<code>\completepublications</code> 70	s
<code>\cr</code> 78	<code>\setupbodyfont</code> 80
d	<code>\setupcolors</code> 87
<code>\definedescription</code> 71	<code>\setuphead</code> 83
<code>\defineenumeration</code> 79	<code>\setupinterlinespace</code> 80
<code>\definestartstop</code> 71	<code>\setupnumbering</code> 82
	<code>\setuppagenumber</code> 83
	<code>\setuppagenumbering</code> 82, 84
	<code>\setuppapersize</code> 79
	<code>\setuppublications</code> 70, 85
	<code>\setupwhitespace</code> 81
i	<code>\startbodymatter</code> 83
<code>\index</code> 85	<code>\startfontmatter</code> 83
<code>\input</code> 66	<code>\startformula</code> 78
	<code>\startitemize</code> 72, 73
m	<code>\startnarrower</code> 69
<code>\midaligned</code> 69	<code>\startpacked</code> 71
	<code>\startpublication</code> 70
n	<code>\startquotation</code> 73
<code>\NC</code> 77	<code>\starttable</code> 76, 77
<code>\NR</code> 77	<code>\starttables</code> 77
	<code>\starttabulate</code> 77
p	<code>\switchtobodyfont</code> 69, 80
<code>\placecontent</code> 68	
<code>\placeformula</code> 78	u
<code>\placelistoffigures</code> 76	<code>\useexternalfigure</code> 75
<code>\placelistoftables</code> 78	

14 L^AT_EX to ConT_EXt reference

14.1 Standard environments

A list of all L^AT_EX environments and the corresponding ConT_EXt environment is provided below. Note that L^AT_EX environments are written as:

```
\begin{environment}
\end{environment}
```

In ConT_EXt you write this as:

```
\startenvironment
\stopenvironment
```

L ^A T _E X environment	ConT _E Xt environment	Remark
abstract	no equivalent.	
array	no equivalent.	
center	alignment	
description		See section 3.3
displaymath		
document	text	
enumerate	itemize	
equation	placeformula	
eqnarray	displaylines	Use the standard T _E X commands.
figure		Use placefigure.
flushleft	alignment	
flushright	alignment	
itemize	itemize	
letter	no equivalent.	
list	itemize	
math		Use \$ before and \$ after the formula.
minipage	no equivalent.	
note	no equivalent.	
overlay	no equivalent.	
picture	MPgraphic	In ConT _E Xt you can include metapost code to achieve the same and better effects.
quote	citaat	
quotation	citaat	
slide	no equivalent.	
sloppypar		
tabbing	tabulate	
table	table	Use together with placetable
tabular	table	
titlepage	no equivalent.	
thebibliography	publication	Requires the bib module.
theindex		Use completeindex.
trivlist	itemize	
verbatim	typing	
verse		

14.2 Standard commands

Many L^AT_EX commands come from third party packages. Most of the things they provide (or fix) are standard features in ConT_EXt.

\LaTeX command	ConTeXt command	Remark
setlanguage		Provided by the babel package.

14.3 Environments provided packages

Many \LaTeX environments come from third party packages. Most of the things they provide (or fix) are standard features in ConTeXt.

\LaTeX package	ConTeXt environment	Remark
comment	comment	Comment out certain parts of your document so it does not show up in the .dvi or .pdf file. \LaTeX 's <code>comment</code> environment is part of Rainer Schöpf's <code>verbatim</code> package.
longtable	tables	The <code>longtable</code> package provides tables that can be broken accross page.